NSN 5305-00-059-4556



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-059-4556 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.008 inches and 1.120 inches **Fastener Length:** Between 1.053 inches and 1.120 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas6000 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A500d0

NSN 5305-00-059-4556

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.