

View Online at <https://aerobasegroup.com/nsn/5305-00-059-5432>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.804 inches and 0.875 inches

Fastener Length:

0.875 inches

Head Style:

Pan

Head Diameter:

Between 0.473 inches and 0.492 inches

Head Height:

Between 0.162 inches and 0.175 inches

Internal Drive Style:

Cross recess type 1

End Application:

W/s: central message switch, an/tyc-39a; close in weapon system (ciws-phalanx); support equipment, b-1 aircraft; aircraft (ac-130h, mc-130h, ec-130e, hc-130); support equipment, b-52 aircraft; missile, air intercept, sidewinder (aim-9); airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a); missile, air-to-air, phoenix (aim-54); missile, tomahawk

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

80000 pounds per square inch

Screw Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Screw Material Specification:

66 federal standard all material responses

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0