NSN 5305-00-059-7660

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-059-7660

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.750 inches |
| Fastener Length: |
| 0.750 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.155 inches and 0.167 inches |
| Head Height: |
| Between 0.053 inches and 0.062 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.086 inches |
| Thready Qty Per Inch (tpi): |
| 56 |
| Min. Tensile Strength (psi): |
| 55000 pounds per square inch |
| Screw Material: |
| Steel comp 1010 or steel comp 1011 or steel comp 1013 |
| Screw Material Specification: |
| 66 federal standard all material responses |
| Screw Surface Treatment: |
| Cadmium |
| Screw Surface Treatment Specification: |
| Qq-p-416, type 2, class 3 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A500d0 |
| |