

View Online at <https://aerobasegroup.com/nsn/5305-00-059-8228>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.214 inches and 0.250 inches

Fastener Length:

Between 0.219 inches and 0.250 inches

Head Style:

Pan

Head Diameter:

Between 0.155 inches and 0.167 inches

Head Height:

Between 0.053 inches and 0.062 inches

Internal Drive Style:

Cross recess type 1

End Application:

W/s: helicopter, search and rescue, hh-60h; tactical air opns module (an/tyq-23)); entry device, program, tam a12757; airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a); helicopter, carrier based asw, sh-60f; helicopter, advance attack, ah-1w; helicopter, mh-53e; helicopter, uscg search and rescue, hh-60j; engine, aircraft, tf39-ge-1 (c-5a)

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

57000 pounds per square inch

Screw Material:

Copper alloy

Screw Material Specification:

Qq-b-626 federal specification single material response or qq-w-321 federal specification single material response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0