

View Online at <https://aerobasegroup.com/nsn/5305-00-059-8228>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.214 inches and 0.250 inches

**Fastener Length:**

Between 0.219 inches and 0.250 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.155 inches and 0.167 inches

**Head Height:**

Between 0.053 inches and 0.062 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

W/s: helicopter, search and rescue, hh-60h; tactical air opns module (an/tyq-23)); entry device, program, tam a12757; airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a); helicopter, carrier based asw, sh-60f; helicopter, advance attack, ah-1w; helicopter, mh-53e; helicopter, uscg search and rescue, hh-60j; engine, aircraft, tf39-ge-1 (c-5a)

**Thread Diameter:**

0.086 inches

**Thready Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

57000 pounds per square inch

**Screw Material:**

Copper alloy

**Screw Material Specification:**

Qq-b-626 federal specification single material response or qq-w-321 federal specification single material response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0