## NSN 5305-00-059-8263

Machine Screw - Page 1 of 1

**Demilitarization:** 

No Fiig: A500d0



View Online at https://aerobasegroup.com/nsn/5305-00-059-8263 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.188 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type 1 **End Application:** W/s: armored security vehicle, model xm1117; radar set, firefinder (an/tpq-36); los angeles class ssn (688); main feed pumps; aircraft, hercules c-130; ticonderoga class cg (47); generator, 10kw, diesel, military standard family; sturgeon class ssn (637); helicopter, advance attack, ah-1w; landing craft, utility, 115 ft **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 57000 pounds per square inch **Screw Material:** Copper alloy **Screw Material Specification:** Qq-b-626 federal specification single material response or qq-w-321 federal specification single material response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**