# NSN 5305-00-059-8263

Machine Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-059-8263

## Thread Class:

2a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.188 inches and 0.250 inches

## Fastener Length:

Between 0.219 inches and 0.250 inches

## Head Style:

Pan

Head Diameter:

Between 0.306 inches and 0.322 inches

## **Head Height:**

Between 0.105 inches and 0.115 inches

Internal Drive Style:

Cross recess type 1

## **End Application:**

W/s: armored security vehicle, model xm1117; radar set, firefinder (an/tpq-36); los angeles class ssn (688); main feed pumps; aircraft, hercules c-130; ticonderoga class cg (47); generator, 10kw, diesel, military standard family; sturgeon class ssn (637); helicopter, advance attack, ah-1w; landing craft, utility, 115 ft

#### **Thread Diameter:**

0.164 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

57000 pounds per square inch

#### **Screw Material:**

Copper alloy

Screw Material Specification:

Qq-b-626 federal specification single material response or qq-w-321 federal specification single material response

#### Thread Series Designator:

Unc

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A500d0

