## NSN 5305-00-060-0402

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-060-0402

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.438 inches  |
| Fastener Length:  |
| 1.688 inches  |
| Head Style:   |
| Flat chamfer  |
| Head Diameter:  |
| Between 0.429 inches and 0.438 inches                       |
| Head Height:  |
| Between 0.213 inches and 0.219 inches                       |
| Shoulder Diameter:  |
| 0.308 inches first shoulder and 0.310 inches first shoulder |
| Shoulder Length:  |
| 1.250 inches first shoulder                                 |
| Internal Drive Style:                                       |
| Hexagon   |
| Thread Diameter:  |
| 0.250 inches  |
| Width Across Flats:   |
| Between 0.156 inches and 0.158 inches                       |
| Thready Qty Per Inch (tpi):                                 |
| 20  |
| Hardness Rating:  |
| 36.0 rockwell c and 43.0 rockwell c                         |
| Minimum Yield Strength:                                     |
| 140000 pounds per square inch                               |
| Shoulder Shape:   |
| Round first shoulder  |
| Material:   |
| Steel   |
| Surface Treatment:  |
| Cadmium and chromate or cadmium and chromate                |
| Thread Series Designator:                                   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

## NSN 5305-00-060-0402

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

