NSN 5305-00-060-3834

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-060-3834

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.020 inches
Fastener Length:
Between 0.990 inches and 1.020 inches
Head Style: Flat chamfer
Head Diameter:
Between 0.739 inches and 0.750 inches
Head Height: Between 0.492 inches and 0.500 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches Width Across Flats:
Between 0.375 inches and 0.378 inches
Thready Qty Per Inch (tpi):
20 Min Toucile Strength (noi)
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 303 or steel comp 304
Material Specification:
Aisi assn standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
-

NSN 5305-00-060-3834

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

