

View Online at <https://aerobasegroup.com/nsn/5305-00-061-1564>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.500 inches

**Fastener Length:**

Between 1.495 inches and 1.505 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.553 inches and 0.562 inches

**Head Height:**

Between 0.244 inches and 0.250 inches

**Shoulder Diameter:**

0.371 inches first shoulder and 0.373 inches first shoulder

**Shoulder Length:**

0.995 inches first shoulder and 1.005 inches first shoulder

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.312 inches

**Width Across Flats:**

Between 0.209 inches and 0.215 inches

**Thready Qty Per Inch (tpi):**

18

**Hardness Rating:**

36.0 rockwell c and 43.0 rockwell c

**Minimum Yield Strength:**

140000 pounds per square inch

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-z-325, type 2, cl 3 federal specification 2nd treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0