## NSN 5305-00-061-1564

Shoulder Screw - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5305-00-061-1564 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** Between 1.495 inches and 1.505 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.553 inches and 0.562 inches **Head Height:** Between 0.244 inches and 0.250 inches **Shoulder Diameter:** 0.371 inches first shoulder and 0.373 inches first shoulder **Shoulder Length:** 0.995 inches first shoulder and 1.005 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.209 inches and 0.215 inches Thready Qty Per Inch (tpi): 18 Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 140000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740 **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-z-325, type 2, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life:

## NSN 5305-00-061-1564

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0