# NSN 5305-00-061-2835

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-061-2835



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### **Thread Length:**

Between 0.888 inches and 0.938 inches

#### Fastener Length:

Between 0.906 inches and 0.938 inches

#### Head Style:

Pan

#### Head Diameter:

Between 0.205 inches and 0.219 inches

#### **Head Height:**

Between 0.070 inches and 0.080 inches

#### Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.112 inches

## Thready Qty Per Inch (tpi):

40

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

#### Screw Material:

Steel comp 8630

#### Screw Material Specification:

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

#### Screw Surface Treatment:

Cadmium and chromate

### Screw Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

#### **Thread Series Designator:**

Unjc

#### Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A500d0

# NSN 5305-00-061-2835

Machine Screw - Page 2 of 2

# Mil-std (military Standard):

Mil-s-6050 spec.

