## NSN 5305-00-061-4760

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-061-4760 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 0.761 inches and 0.791 inches **Head Style:** Pan **Head Diameter:** Between 0.361 inches and 0.385 inches **Head Height:** Between 0.103 inches and 0.118 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.192 inches **Grip Length:** 0.500 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: 248.0 brinell standard and 321.0 brinell standard **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

**Specification Data:** 

80205-nas1143 professional/industrial association standard

## NSN 5305-00-061-4760

Close Tolerance Screw - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0