NSN 5305-00-061-6349

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-061-6349 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.293 inches and 0.343 inches **Fastener Length:** Between 0.928 inches and 0.958 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Shoulder Diameter:** 0.193 inches first shoulder and 0.195 inches first shoulder **Shoulder Length:** 0.615 inches first shoulder and 0.635 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 8630 or steel comp 4037 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-061-6349

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0