NSN 5305-00-063-3837

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-063-3837 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.219 inches and 0.357 inches **Fastener Length:** Between 1.362 inches and 1.409 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.502 inches and 0.507 inches **Shoulder Diameter:** 0.264 inches first shoulder and 0.265 inches first shoulder **Shoulder Length:** 0.950 inches first shoulder and 0.972 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp 4130 or steel comp 4037 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification all treatment responses **Thread Series Designator:**

Shelf Life:

Unf

N/a

Unit Of Measure:

NSN 5305-00-063-3837

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0