NSN 5305-00-063-3840 Shoulder Screw - Page 1 of 2

N/a



/iew Online at https://aerobasegroup.com/nsn/5305-00-063-3840
Thread Class:
3a
Thread Direction:
Right-hand
Гhread Length:
Between 0.219 inches and 0.357 inches
Fastener Length:
Between 0.988 inches and 1.035 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.502 inches and 0.507 inches
Shoulder Diameter:
0.264 inches and 0.265 inches first shoulder
Shoulder Length:
0.576 inches and 0.598 inches first shoulder
nternal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Гhready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Shoulder Shape:
Round first shoulder
Product Name:
Navy special project
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp
4130 or steel comp 4037
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification all treatment responses
Thread Series Designator:
Jnf
Shelf Life:

NSN 5305-00-063-3840

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0