NSN 5305-00-064-0206

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-064-0206

-
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.230 inches
Fastener Length:
0.390 inches
Head Style:
Flat countersunk
Head Diameter:
0.223 inches
Shoulder Diameter:
0.141 inches first shoulder and 0.143 inches first shoulder
Shoulder Length:
0.122 inches first shoulder
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
32 Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 150000 pounds per square inch
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees Shoulder Shape:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees Shoulder Shape: Round first shoulder
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees Shoulder Shape: Round first shoulder Material:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees Shoulder Shape: Round first shoulder Material: Steel
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees Shoulder Shape: Round first shoulder Material: Steel Surface Treatment:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees Shoulder Shape: Round first shoulder Material: Steel Surface Treatment: Cadmium
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees Shoulder Shape: Round first shoulder Material: Steel Surface Treatment: Cadmium Thread Series Designator:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees Shoulder Shape: Round first shoulder Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees Shoulder Shape: Round first shoulder Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life:
Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees Shoulder Shape: Round first shoulder Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a

No

NSN 5305-00-064-0206

Shoulder Screw - Page 2 of 2



Fiig:

A003b0