NSN 5305-00-064-0206

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-064-0206

| Thread Class: 2a Thread Direction: Right-hand Thread Length: 0.230 inches Fastener Length: 0.390 inches Fastener Length: 0.390 inches Head Style: Flat countersunk Head Diameter: 0.223 inches Shoulder Diameter: 0.223 inches Shoulder Diameter: 0.141 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: 100.0 degrees |
|---|
| Thread Direction:Right-handThread Length:0.230 inchesFastener Length:0.390 inchesHead Style:Flat countersunkHead Diameter:0.223 inchesShoulder Diameter:0.141 inches first shoulder and 0.143 inches first shoulderShoulder Length:0.122 inches first shoulderInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):150000 pounds per square inchHardness Rating:33.0 rockwell c and 37.0 rockwell cCountersink Angle: |
| Right-handThread Length:0.230 inchesFastener Length:0.390 inchesHead Style:Flat countersunkHead Diameter:0.223 inchesShoulder Diameter:0.122 inchesShoulder Length:0.141 inches first shoulder and 0.143 inches first shoulderShoulder Length:0.122 inches first shoulderInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):150000 pounds per square inchHardness Rating:33.0 rockwell c and 37.0 rockwell cCountersink Angle: |
| Thread Length:0.230 inchesFastener Length:0.390 inchesHead Style:Flat countersunkHead Diameter:0.223 inchesShoulder Diameter:0.123 inchesShoulder Diameter:0.141 inches first shoulder and 0.143 inches first shoulderShoulder Length:0.122 inches first shoulderInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):150000 pounds per square inchHardness Rating:33.0 rockwell c and 37.0 rockwell cCountersink Angle: |
| 0.230 inches Fastener Length: 0.390 inches Head Style: Flat countersunk Head Diameter: 0.223 inches Shoulder Diameter: 0.223 inches Shoulder Diameter: 0.141 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.142 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder Hrterad Diameter: 0.138 inches Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c |
| Fastener Length:0.390 inchesHead Style:Flat countersunkHead Diameter:0.223 inchesShoulder Diameter:0.141 inches first shoulder and 0.143 inches first shoulderShoulder Length:0.122 inches first shoulderInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):150000 pounds per square inchHardness Rating:33.0 rockwell c and 37.0 rockwell cCountersink Angle: |
| 0.390 inches Head Style: Flat countersunk Head Diameter: 0.223 inches Shoulder Diameter: 0.141 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.141 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder Noter Style: 0.123 inches first shoulder Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c_and 37.0 rockwell c |
| Head Style:Flat countersunkHead Diameter:0.223 inchesShoulder Diameter:0.141 inches first shoulder and 0.143 inches first shoulderShoulder Length:0.122 inches first shoulderInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):150000 pounds per square inchHardness Rating:33.0 rockwell c and 37.0 rockwell cCountersink Angle: |
| Flat countersunk Head Diameter: 0.223 inches Shoulder Diameter: 0.141 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c |
| Head Diameter:0.223 inchesShoulder Diameter:0.141 inches first shoulder and 0.143 inches first shoulderShoulder Length:0.122 inches first shoulderInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):150000 pounds per square inchHardness Rating:33.0 rockwell c and 37.0 rockwell cCountersink Angle: |
| 0.223 inches Shoulder Diameter: 0.141 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c |
| Shoulder Diameter: 0.141 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: |
| 0.141 inches first shoulder and 0.143 inches first shoulder Shoulder Length: 0.122 inches first shoulder Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: |
| Shoulder Length:0.122 inches first shoulderInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):150000 pounds per square inchHardness Rating:33.0 rockwell c and 37.0 rockwell cCountersink Angle: |
| 0.122 inches first shoulder Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c_and 37.0 rockwell c Countersink Angle: |
| Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c_and 37.0 rockwell c |
| Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: |
| Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):150000 pounds per square inchHardness Rating:33.0 rockwell c and 37.0 rockwell cCountersink Angle: |
| 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: |
| Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: |
| 32 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: |
| Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: |
| 150000 pounds per square inch Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: |
| Hardness Rating: 33.0 rockwell c and 37.0 rockwell c Countersink Angle: |
| 33.0 rockwell c and 37.0 rockwell c Countersink Angle: |
| - |
| 100.0 degrees |
| 100:0 degrees |
| Shoulder Shape: |
| Round first shoulder |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5305-00-064-0206

Shoulder Screw - Page 2 of 2

Fiig: A003b0

