## NSN 5305-00-065-6337

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-065-6337 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.350 inches **Fastener Length:** Between 0.910 inches and 0.930 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.290 inches and 0.310 inches **Head Height:** Between 0.050 inches and 0.060 inches **First Diameter From Head:** Between 0.192 inches and 0.196 inches **Second Diameter From Head:** Between 0.156 inches and 0.160 inches Third Diameter From Head: Between 0.192 inches and 0.196 inches **Fourth Diameter From Head:** Between 0.156 inches and 0.160 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.160 inches and 0.180 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 4 Material: Steel **Material Specification:** Qq-s-624 federal specification single material response **Surface Treatment:** Chromium

**Surface Treatment Specification:** 

Mil-std 171, fin. 1.2.2 military standard single treatment response

## NSN 5305-00-065-6337

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

spec.