## NSN 5305-00-066-7336

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-066-7336 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.558 inches and 0.625 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.136 inches and 0.140 inches **Head Height:** Between 0.044 inches and 0.053 inches **Locking Feature:** Pellet threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-00-066-7336

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.