Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-067-8016

| Thread Class:   |
|---|
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.395 inches  |
| Fastener Length:  |
| 0.635 inches  |
| Head Diameter:  |
| 1.125 inches  |
| Head Height:  |
| 0.185 inches  |
| Point Length:   |
| 0.180 inches  |
| Point Diameter:   |
| 0.500 inches  |
| First Diameter From Head:   |
| 0.670 inches  |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.060 inches  |
| Thread Diameter:  |
| 0.750 inches  |
| Thready Qty Per Inch (tpi):   |
| 16  |
| Hole Thready Qty Per Inch (tpi):  |
| 40  |
| Hole Configuration Style:   |
| Round perpendicular   |
| Externally Relieved Body Diameter Quantity:                             |
| 1   |
| Hole Thread Diameter:   |
| 0.112 inches  |
| Special Features:   |
| Axial hole in point 0.234 in. Diax 0.406 in. Deep                       |
| Material:   |
| Aluminum alloy 2024 or aluminum alloy 6061                              |
| Material Specification:   |
| Qq-a-225/6 tp 4 or tp 6 federal specification all material responses    |
| Surface Treatment:  |
| Enamel head   |
| Surface Treatment Specification:  |
| Fed-std-595 olive drab federal standard single treatment response head  |

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0