## NSN 5305-00-067-9916

**Thread Class:** 

Right-hand
Thread Length:
0.308 inches
Fastener Length:

0.375 inches **Head Style:** 

**Thread Direction:** 

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-067-9916

rial cri	amfer
Head I	Diameter:
Betwee	en 0.303 inches and 0.312 inches
Head I	Height:
Betwee	en 0.185 inches and 0.190 inches
Hole D	Diameter:
0.047 i	inches
Intern	al Drive Style:
Hexag	on
Threa	d Diameter:
0.190 i	inches
Width	Across Flats:
0.157 i	inches
Hole C	Quantity:
6	
Hole T	уре:
Drilled	
Threa	dy Qty Per Inch (tpi):
24	
Min. T	ensile Strength (psi):
85000	pounds per square inch
Minim	um Yield Strength:
30000	pounds per square inch
Hole C	Configuration Style:
Round	internal hexagon
Cham	fer Angle:
Betwe	en 30.0 degrees and 45.0 degrees
Materi	al:
Stainle	ess steel
Materi	al Specification:
66 fed	eral standard single material response
Surfac	ce Treatment:
Passiv	ate

## NSN 5305-00-067-9916

Socket Head Cap Screw - Page 2 of 2



Surface Treatment S	pecification:
---------------------	---------------

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0