

View Online at <https://aerobasegroup.com/nsn/5305-00-068-0510>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.000 inches

Fastener Length:

1.000 inches

Head Style:

Hexagon

Head Height:

Between 0.226 inches and 0.243 inches

Width Between Flats:

Between 0.551 inches and 0.562 inches

End Application:

Mrap-rg-33; rg-33 auv; mrap buffalo mk2a2; m-atv w/cs13 pop; mrap - cougar cat1 a2; medium mine protected vehicle - mmpv

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

33.0 rockwell c and 39.0 rockwell c

Minimum Yield Strength:

120000 pounds per square inch

Material:

Steel

Material Specification:

Saej429 grade 8 assn standard single material response or astm a354 grade bd assn standard single material response

Surface Treatment:

Zinc and chromate

Surface Treatment Specification:

Astm b633 type 2 sc 3 assn standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0