NSN 5305-00-068-1803

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-068-1803 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.301 inches **Fastener Length:** 1.500 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Spec item **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 62000 pounds per square inch **Screw Material:** Aluminum alloy 2024 or aluminum alloy 2017 **Screw Material Specification:** Qq-a-200/3 federal specification 1st material response or qq-a-225/6 federal specification 1st material response or qq-a-225/5 federal specification 2nd material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-068-1803

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.