NSN 5305-00-068-1812

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-068-1812

| view Online at https://aerobasegroup.com/hsi//3303-00-000 |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.750 inches |
| Fastener Length: |
| 2.500 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.473 inches and 0.492 inches |
| Head Height: |
| Between 0.162 inches and 0.175 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 62000 pounds per square inch |
| Screw Material: |
| Aluminum alloy 2024 |
| Screw Material Specification: |
| Qq-a-225/6 federal specification single material response |
| Screw Surface Treatment: |
| Anodize |
| Screw Surface Treatment Specification: |
| Mil-a-8625 military specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A500d0 |
| Mil-std (military Standard): |
| Mil-a-8625 spec. |