NSN 5305-00-068-5371

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-068-5371

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.341 inches and 0.361 inches **Fastener Length:** Between 1.460 inches and 1.507 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.625 inches and 0.635 inches **Grip Diameter:** Between 0.3108 inches and 0.3117 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp h11 **Material Specification:** Ams6485 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Test Data Document:** 84955-k611641 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Unjf

Thread Series Designator:

NSN 5305-00-068-5371

Close Tolerance Screw - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0