NSN 5305-00-068-5396

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-068-5396 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.387 inches and 0.419 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.263 inches and 0.307 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.0781 inches and 0.0791 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Countersink Angle:** 82.0 degrees Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-068-5396

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0