

NSN 5305-00-068-5398 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-068-5398 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.283 inches and 0.375 inches **Fastener Length:** Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Hole Diameter:** 0.047 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

**Hole Configuration Style:** 

Round

Material:

Stainless steel

**Material Specification:** 

66 federal standard single material response

**Surface Treatment:** 

**Passivate** 

## NSN 5305-00-068-5398

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0