NSN 5305-00-068-5400

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-068-5400



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.607 inches and 0.639 inches Fastener Length: Between 0.734 inches and 0.766 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.359 inches and 0.411 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.125 inches and 0.127 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c **Minimum Yield Strength:** 130000 pounds per square inch **Countersink Angle:** 82.0 degrees Material: Steel Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No

NSN 5305-00-068-5400

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

