NSN 5305-00-068-5829



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-068-5829 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.282 inches **Fastener Length:** 0.438 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 62000 pounds per square inch **Screw Material:** Aluminum alloy 2024 or aluminum alloy or aluminum alloy 2024 **Screw Material Specification:** Qq-a-200/3 federal specification 1st material response or qq-a-225/5 federal specification 2nd material response or qq-a-225/6 federal specification 3rd material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A500d0

No

NSN 5305-00-068-5829

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.