NSN 5305-00-068-5838

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-068-5838

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.125 inches
Fastener Length: Between 1.484 inches and 1.531 inches
Head Style: Flat chamfer
Head Diameter:
Between 0.457 inches and 0.468 inches
Head Height:
Between 0.306 inches and 0.312 inches
Hole Diameter:
0.062 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
Between 0.250 inches and 0.253 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 43.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Hole Configuration Style:
Round
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response

NSN 5305-00-068-5838

Socket Head Cap Screw - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

