## NSN 5305-00-068-5842

Socket Head Cap Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-068-5842

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 1.340 inches and 1.610 inches	
Fastener Length:	
Between 2.460 inches and 2.500 inches	
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.457 inches and 0.469 inches	
Head Height:	
Between 0.306 inches and 0.312 inches	
Hole Diameter:	
0.047 inches	
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.312 inches	
Width Across Flats:	
Between 0.250 inches and 0.253 inches	
Hole Quantity:	
6	
Ноје Туре:	
Drilled	
Thready Qty Per Inch (tpi):	
24	
Min. Tensile Strength (psi):	
170000 pounds per square inch	
Hardness Rating:	
38.0 rockwell c and 45.0 rockwell c	
Minimum Yield Strength:	
150000 pounds per square inch	
Hole Configuration Style:	
Round	
Special Features:	
Material could use any comp which can be heat treated in accordance with mil-h-6875	
Material:	
Steel	
Material Specification:	

66 federal standard single material response

## NSN 5305-00-068-5842

Socket Head Cap Screw - Page 2 of 2



Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unf **Specification Or Standard:** 4 type Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A003b0