NSN 5305-00-068-7064

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-068-7064

| Т | hread Class: |
|----|--|
| 2 | a |
| Т | hread Direction: |
| R | light-hand |
| Т | hread Length: |
| 0 | .437 inches |
| F | astener Length: |
| 0 | .437 inches |
| Н | lead Style: |
| F | illister |
| Н | lead Diameter: |
| B | etween 0.250 inches and 0.320 inches |
| Н | lead Height: |
| В | etween 0.106 inches and 0.113 inches |
| Н | lole Diameter: |
| 0 | .046 inches |
| Ir | nternal Drive Style: |
| S | lot |
| т | hread Diameter: |
| 0 | .164 inches |
| Н | lole Quantity: |
| 1 | |
| т | hready Qty Per Inch (tpi): |
| 3 | 2 |
| N | lin. Tensile Strength (psi): |
| 6 | 2000 pounds per square inch |
| S | crew Material: |
| A | luminum alloy 2024 |
| S | crew Material Specification: |
| C | Qq-a-225/6 federal specification single material response |
| S | crew Surface Treatment: |
| С | Dxide film |
| S | crew Surface Treatment Specification: |
| N | il-c-5541 military specification single treatment response |
| Η | lead Hole Configuration Style: |
| R | lound |
| т | hread Series Designator: |
| ι | Inc |
| S | helf Life: |
| Ν | l/a |
| U | Init Of Measure: |
| | |

NSN 5305-00-068-7064

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-5541 spec.

