Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-068-8340

| View Online at https://aerobasegroup.com/nsn/5305-00-068-8340 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.500 inches |
| Fastener Length: |
| 2.280 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| 0.312 inches |
| Head Height: |
| 0.123 inches |
| Hole Diameter: |
| 0.046 inches |
| First Diameter From Head: |
| Between 0.199 inches and 0.200 inches |
| Second Diameter From Head: |
| Between 0.117 inches and 0.127 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 1.620 inches |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 1.780 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.190 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Hole Configuration Style: |
| Round |
| Externally Relieved Body Diameter Quantity: |
| 2 |
| Material: |
| Steel comp 304 |
| Material Specification: |

Qq-s-763 federal specification single material response

Externally Relieved Body Screw - Page 2 of 2

Surface Treatment:

Passivate

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

