NSN 5305-00-069-2576

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-069-2576

Thread Class:

2a
Thread Direction:
Right-hand
Thread Length:
Between 0.240 inches and 0.302 inches
Fastener Length:
Between 0.302 inches and 0.322 inches
Head Style:
Fillister
Head Diameter:
Between 0.208 inches and 0.226 inches
Head Height:
Between 0.144 inches and 0.154 inches
Hole Diameter:
0.046 inches
Internal Drive Style:
Slot
Thread Diameter:
0.138 inches
Hole Quantity:
2
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32
32
32 Min. Tensile Strength (psi):
32 Min. Tensile Strength (psi): 70000 pounds per square inch
32 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material:
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material: Steel
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material: Steel Screw Material Specification:
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material: Steel Screw Material Specification: Ams 5061 assn standard single material response
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material: Steel Screw Material Specification: Ams 5061 assn standard single material response Screw Surface Treatment:
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material: Steel Screw Material Specification: Ams 5061 assn standard single material response Screw Surface Treatment: Cadmium
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material: Steel Screw Material Specification: Ams 5061 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification:
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material: Steel Screw Material Specification: Ams 5061 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material: Steel Screw Material Specification: Ams 5061 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style:
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material: Steel Screw Material Specification: Ams 5061 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style: Hexagon flats
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material: Steel Screw Material Specification: Ams 5061 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style: Hexagon flats Thread Series Designator:
Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: Between 80.0 rockwell b and 100.0 rockwell b Screw Material: Steel Screw Material Specification: Ams 5061 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style: Hexagon flats Thread Series Designator: Unc

NSN 5305-00-069-2576

Machine Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A500d0