NSN 5305-00-070-6013

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-070-6013 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.287 inches and 0.337 inches **Fastener Length:** Between 0.772 inches and 0.802 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.408 inches and 0.531 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4130 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Special Features:** Internal hole in head 0.190 in. Nom dia, 32 thds per in., unf class 3b, countersunk 90 degrees **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A500d0