

View Online at <https://aerobasegroup.com/nsn/5305-00-071-1318>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.900 inches and 1.000 inches

**Fastener Length:**

1.000 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.473 inches and 0.492 inches

**Head Height:**

Between 0.162 inches and 0.175 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

Stream (std. Tensioned replenishment at sea method); missile systems, nato sea sparrow; support equipment, b-52 aircraft; aircraft, ( ac-130h, mc; mrap cougar ambulance; mrap buffalo mk2a2

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Screw Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

**Screw Material Specification:**

66 federal standard all material responses

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0