NSN 5305-00-071-1944

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-071-1944

| ٦ | Fhread Class: |
|---|--|
| Э | Ba |
| ٦ | Thread Direction: |
| F | Right-hand |
| ٦ | Thread Length: |
| 1 | .062 inches |
| F | Fastener Length: |
| 1 | .062 inches |
| ŀ | lead Style: |
| F | Tat chamfer |
| ŀ | lead Diameter: |
| E | Between 0.304 inches and 0.312 inches |
| ŀ | lead Height: |
| E | Between 0.185 inches and 0.190 inches |
| I | nternal Drive Style: |
| ŀ | lexagon |
| ٦ | Thread Diameter: |
| C | 0.190 inches |
| ۷ | Vidth Across Flats: |
| C | 0.156 inches |
| ٦ | Thready Qty Per Inch (tpi): |
| 3 | 32 |
| N | Naterial: |
| S | Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 316 |
| N | Naterial Specification: |
| | 6 federal standard all material responses |
| S | Surface Treatment: |
| - | Passivate |
| ٦ | Thread Series Designator: |
| | Jnf |
| | Shelf Life: |
| - | √a |
| ι | Jnit Of Measure: |
| - | |
| | Demilitarization: |
| | No |
| | filg: |
| A | A003b0 |
| | |
| | |