

View Online at <https://aerobasegroup.com/nsn/5305-00-071-2056>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.125 inches and 1.312 inches

Fastener Length:

Between 1.688 inches and 1.750 inches

Head Height:

Between 0.272 inches and 0.291 inches

Width Between Flats:

Between 0.612 inches and 0.625 inches

End Application:

0aircraft, c-2 (reprocured); helicopter mh-53e; helicopter, advance attack; generator set, diesel engine; decontaminating apparatus; helicopter, carrier based asw; helicopter uscg; crane (rt41aa); nsn 4210-01-486-1035 tfft (tactical fire fighting truck)

Thread Diameter:

0.438 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

150000 pounds per square inch

Surface Finish:

63.0 microinches threads

Material:

Steel

Material Specification:

Sae j429 grade 8 assn standard single material response or astm a354 grade bd assn standard single material response

Surface Treatment:

Zinc and chromate

Surface Treatment Specification:

Astm b633 type 2 sc 3 assn standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0