

View Online at <https://aerobasegroup.com/nsn/5305-00-071-2067>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.250 inches

Fastener Length:

1.250 inches

Head Style:

Hexagon

Head Height:

Between 0.302 inches and 0.323 inches

Width Between Flats:

Between 0.736 inches and 0.750 inches

End Application:

Contact maintenance truck, b-1 support equipment, aircraft refueler vehicle, boilers, compressors, firepumps, stream, shipboard material handling eq, mk-48 torpedo; rg-33 armored utility vehicle (auv); rg-33 mrp

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

13

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

33.0 rockwell c and 39.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Material:

Steel

Material Specification:

Sae j429, grade 8 assn standard single material response or astm a354, grade bd assn standard single material response

Surface Treatment:

Zinc and chromate

Surface Treatment Specification:

Astm b633 type 2 sc 3 assn standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-1222 spec.