

View Online at <https://aerobasegroup.com/nsn/5305-00-072-4523>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.733 inches and 0.765 inches

Fastener Length:

Between 0.984 inches and 1.016 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.872 inches and 0.937 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.500 inches

Width Across Flats:

Between 0.313 inches and 0.316 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 43.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Special Features:

Hole along longitudinal axis 0.092 in. Min, 0.099 in. Maximum diameter from bottom of socket to the thd end of fastener

Material:

Steel

Material Specification:

66 federal standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0