## NSN 5305-00-074-1989

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-074-1989 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.450 inches **Fastener Length:** 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.200 inches and 0.225 inches Width Between Flats: Between 0.200 inches and 0.225 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 62000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Aluminum alloy 2024 or aluminum alloy 2017 **Screw Material Specification:** Qq-a-200/3 federal specification 1st material response or qq-a-225/6 federal specification 1st material response or qq-a-225/5 federal specification 2nd material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 1 type and 2s style Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-00-074-1989

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.