NSN 5305-00-074-2698

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-074-2698

View Online at https://aerobasegroup.com/nsn/5305-00-074-2698
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.366 inches and 0.416 inches
Fastener Length:
Between 1.126 inches and 1.156 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.704 inches and 0.762 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.375 inches
Grip Length:
Between 0.740 inches and 0.760 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, ty2, cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1156 professional/industrial association standard
Shelf Life:
OHOR ERG.

N/a

NSN 5305-00-074-2698

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0