NSN 5305-00-078-0184

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-078-0184



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.510 inches and 1.620 inches

Fastener Length:

Between 1.560 inches and 1.620 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Screw Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military

specification 3rd material response

Screw Surface Treatment:

Cadmium and chromate

Thread Series Designator:

Unjc

Specification Data:

80205-nas600 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

NSN 5305-00-078-0184

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-5626 spec.

