NSN 5305-00-079-2867



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-079-2867 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.560 inches **Fastener Length:** 5.190 inches **Head Style:** Fillister **Head Diameter:** 0.310 inches **Head Height:** 0.130 inches **Shoulder Diameter:** 0.156 inches first shoulder **Shoulder Length:** 4.630 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.063 inches first hole and 0.066 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Distance From Head Largest Bearing Surface To Shank Hole Center: 0.718 inches first hole **Shoulder Shape:** Round first shoulder **Special Features:** W/non standard point style 10 a-0.062 in long c-0.093 in dia Material: Steel comp 303se **Material Specification:** Astm a582, cond b assn standard single material response **Surface Treatment: Passivate**

Surface Treatment Specification:

Qq-p-35, type 2 federal specification single treatment response

Thread Series Designator:

Unc

NSN 5305-00-079-2867

Shoulder Screw - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0