NSN 5305-00-080-0744

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-080-0744 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.200 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.183 inches **Head Height:** Between 0.072 inches and 0.079 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 430 **Screw Material Specification:** Qq-s-763, class 4 federal specification single material response or mil-s-7720, comp fm or g military specification single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Data:** 81348-ff-s-92 government specification and 88044-an500/canceled/ government standard and 96906-ms35366/canceled/ government standard **Specification Or Standard:** 3 type and 4c style and 4-40 size Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-080-0744

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-7720 spec.