

View Online at <https://aerobasegroup.com/nsn/5305-00-080-3900>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.266 inches

Fastener Length:

1.812 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.229 inches and 0.239 inches

Head Height:

0.423 inches

First Diameter From Head:

Between 0.116 inches and 0.118 inches

Second Diameter From Head:

Between 0.229 inches and 0.239 inches

Third Diameter From Head:

0.125 inches

Fourth Diameter From Head:

Between 0.229 inches and 0.239 inches

Fifth Diameter From Head:

Between 0.139 inches and 0.149 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.028 inches and 0.031 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.092 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

0.921 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

0.983 inches

Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:

1.123 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

5

Product Name:

Navy special project

Material:

Steel comp 303

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0