NSN 5305-00-080-3900

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-080-3900 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.266 inches **Fastener Length:** 1.812 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.229 inches and 0.239 inches **Head Height:** 0.423 inches **First Diameter From Head:** Between 0.116 inches and 0.118 inches **Second Diameter From Head:** Between 0.229 inches and 0.239 inches Third Diameter From Head: 0.125 inches **Fourth Diameter From Head:** Between 0.229 inches and 0.239 inches Fifth Diameter From Head: Between 0.139 inches and 0.149 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.028 inches and 0.031 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.092 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.921 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: 1.123 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi):

Externally Relieved Body Diameter Quantity: 5

NSN 5305-00-080-3900

Externally Relieved Body Screw - Page 2 of 2



Product Name:
Navy special project
Material:
Steel comp 303
Material Specification:
Qq-s-763 federal specification single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0