# NSN 5305-00-082-1675

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-082-1675



# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 1.313 inches and 1.438 inches

#### Fastener Length:

Between 1.375 inches and 1.438 inches

#### Head Style:

Pan

#### Head Diameter:

Between 0.357 inches and 0.373 inches

#### **Head Height:**

Between 0.122 inches and 0.133 inches

#### Internal Drive Style:

Cross recess type 1

### Thread Diameter:

0.190 inches

### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

#### Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

#### Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military

specification 3rd material response

#### Screw Surface Treatment:

Cadmium and chromate

#### Screw Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

#### Thread Series Designator:

Unjf

#### **Specification Data:**

80205-nas603 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5305-00-082-1675

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-5626 spec.

