NSN 5305-00-082-1894

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-082-1894 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.167 inches **Fastener Length:** 0.312 inches **Head Style:** Fillister **Head Diameter:** Between 0.187 inches and 0.205 inches **Head Height:** Between 0.081 inches and 0.088 inches **Hole Diameter:** 0.031 inches First Diameter From Head: Between 0.098 inches and 0.102 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.135 inches and 0.145 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.125 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 40 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 304 or steel comp 316 or steel comp 303se **Material Specification:** 66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or astm a582 assn standard 4th material response **Surface Treatment:**

Unc

Passivate

Thread Series Designator:

NSN 5305-00-082-1894

Externally Relieved Body Screw - Page 2 of 2



		fe:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0